

fraction thereof, but the number of berths need not exceed 6.

(6) The crew spaces must be securely constructed, properly lighted, heated, drained, ventilated, equipped, located, and arranged, and, practicable, must be insulated from undue noise and odors.

(c) Vessels of 100 gross tons and over, contracted for on or after January 1, 1941, but prior to November 19, 1952, must meet the requirements of this paragraph.

(1) Existing structure, arrangements, materials, and facilities, previously accepted or approved will be considered satisfactory so long as they are maintained in a good condition to the satisfaction of the Office in Charge, Marine Inspection. Minor repairs and alterations may be made to the same standard as the original construction.

(2) There must be a minimum of 1 toilet, 1 shower, and 1 washbasin for each 8 members of the crew or fraction thereof who are not accommodated in rooms having attached private or semi-private facilities. Washbasins, showers, and bathtubs, if substituted for showers, must be equipped with adequate plumbing, including hot and cold running water.

(3) Crew spaces must have a volume of at least 3.4 cubic meters (120 cubic feet) and a deck of at least 1.5 square meters (16 square feet) for each person accommodated.

(4) Each crewmember shall have a separate berth, and berths may not be placed more than two high.

(5) Each vessel, which in the ordinary course of its trade makes a voyage of more than 3 days duration between ports and which carries a crew of 12 or more persons, must be provided with a suitable hospital space for the exclusive use of the sick or injured. Berths must be provided in the ratio of 1 berth for each 12 members of the crew or fraction thereof, but the member of berths need not exceed 6.

(6) The crew spaces must be securely constructed, properly lighted, heated, drained, ventilated, equipped, located, and arranged, and, where practicable, must be insulated from undue noise heat, and odors.

[CGD 95–027, 61 FR 26002, May 23, 1996; 61 FR 35138, July 5, 1996]

Subpart 72.25—Passenger Accommodations

§ 72.25–1 Application.

(a) The provisions of this subpart shall apply to all vessels.

(b) [Reserved]

§ 72.25–10 Location of passenger quarters.

(a) The deck forming the deckhead of passenger quarters between adjacent watertight bulkheads shall not be below the deepest load line at any point within the watertight compartment in question.

(b) [Reserved]

§ 72.25–15 Passenger accommodations for excursion boats, ferryboats, and passenger barges.

(a) Except as specifically excluded by this section, separate public toilet spaces shall be provided for male and female passengers with at least the minimum equipment in each based upon the number of passengers permitted to be carried as set forth in table 72.25–15(a).

TABLE 72.25–15(a)

| Number of passengers | | Toilets | Wash-basins |
|----------------------|----------|------------------|------------------|
| Over | Not over | | |
| | 100 | 1 | 1 |
| 100 | 300 | 2 | 1 |
| 300 | 500 | 3 | 2 |
| 500 | 1,000 | 4 | 2 |
| 1,000 | 1,500 | 5 | 3 |
| 1,500 | 2,000 | 6 | 3 |
| 2,000 | 2,500 | 7 | 4 |
| 2,500 | 3,000 | 8 | 4 |
| 3,000 | 3,500 | 9 | 5 |
| 3,500 | 4,000 | 10 | 5 |
| 4,000 | | (¹) | (¹) |

¹ Additional facilities by extrapolation.

(b) In the men's spaces, urinals may be substituted for toilets, provided at least one-half the required toilets are fitted.

(c) On ferryboats and barges having a short run, passenger toilet facilities need not be fitted.